



Technical Data Sheet

Product: Finger Jet

Product Code: 15 Series



- NCA's range of bronze finger jets provides a fan shape jet streams of water.
- Constructed in Bronze to AS836B, BS LG2 and JIS BC6 standards.
- 15 series Jets contain two large cleaning holes on each side of the jet. These are covered by bonded access covers.
- The 15-VA-25 Jet has 25 fingers machined into the top with long passage ways.
- NCA recommend the use of 2.5mm aperture screen over the pump pit or in suction strainer basket to prevent clogging.


over the pump pit or in suction strainer basket to prevent clogging.

- If a swivel flange is required with a 15-VA-25 jet please order 15-VB-25.
- This jet can be manufactured to provide a 4mm wide slot providing a fan display. The fan model number is 15-VC-25.
- 15-VA-25 performance figures for jet angles of 90degrees (values relative to jet head level):



Height (M)	Display Width (M)	Flow (LPM)	Pressure at Jet (M)
0.5	1.8	32	1.7
1.0	2.8	48	1.9
1.5	5.0	58	2.4
2.0	6.6	66	3.1

- 15-VA-25 performance figures for jet angles of 45degrees (values relative to jet head level):



Height (M)	Display Width (M)	Spray Trajectory (M)	Flow (LPM)	Pressure at Jet (M)
0.4	2.5	2.0	46	1.6
0.6	3.1	3.5	58	2.5
0.7	3.6	3.8	66	3.6
0.9	5.2	5.1	78	4.9