



Technical Data Sheet

Product: Adjustable Flanges
Product Code: 2-AF Series



- NCA's Adjustable Flanges are designed to correct vertical adjustments of spray jets and nozzles, without swivel bases, up to 5 degrees off vertical.
- The flanges have male / female threaded connections and are manufactured from Bronze and Stainless steel bolts used to provide the adjustment required.
- Adjustment ± 2.5 degrees.
- These flanges are designed for installation below water level.

- **Models available:**

Model	Flange Diameter (mm)	Flange height (mm)	Thread Size
2-AF-12	85	59	1/2" BSP/NPT
2-AF-20	85	59	3/4" BSP/NPT
2-AF-25	100	63	1" BSP/NPT
2-AF-32	112	66	1 1/4" BSP/NPT
2-AF-40	112	73	1 1/2" BSP/NPT
2-AF-50	115	82	2" BSP/NPT
2-AF-65	131	82	2 1/2" BSP/NPT
2-AF-80	165	91	3" BSP/NPT
2-AF-100	199	170	4" BSP/NPT
2-AF-150	248	255	6" BSP/NPT

- **Installation**

1. Submerge the adjustable flange below water level,
2. Adjust jet by loosening the bolt opposite to required location,
3. Use riser pipes – 20mm for 1/2", 3/4" & 1"; 30mm for 1 1/4", 1 1/2" & 2"; 50mm for 3", 4" & 6" thread sizes.