



Technical Data Sheet

Product: Bell Jets
Product Code: 4 Series



- The NCA Bell jets provide a clear beautiful clear bell shape display.
 - The Bell jets come in a number of standard heights for both ½” and 1” models – refer to table below.
 - The Base and cone deflector is made from cast navel gunmetal to AS/NZ 836B, JIS.B6 and BS.LG2 standards, copper tube and type 304 stainless steel all thread and securing screw.
- Jet finish can be raw, painted or zinc plated at extra cost.
 - Tripod stand is available for both model sizes – i.e. 4-BS-12 for ½” models and 4-BS-25 for 1” models.
 - The display is adjustable by loosening the top securing screw and adjusting the cone up or down the internal thread. Adjusting the cone down increases the diameter of the display. Valves are not required for flow control.

Model and Specifications:

Model	Height (mm)	Thread Size BSPF	Cone Diameter (mm)	Approx Display Diameter (mm)	Flow (LPM)	Pressure at Jet (M)
4-BA-12	170	½”	57	200 ~ 800	6 ~ 30	0.8 ~ 1.2
4-BB-12	230	½”	57	200 ~ 800	6 ~ 30	0.8 ~ 1.2
4-BC-12	310	½”	57	200 ~ 800	6 ~ 30	0.8 ~ 1.2
4-BD-25	310	1”	84	600 ~ 1200	20 ~ 50	1.5 ~ 2.6
4-BE-25	450	1”	84	600 ~ 1200	20 ~ 50	1.5 ~ 2.6
4-BF-25	600	1”	84	600 ~ 1200	20 ~ 50	1.5 ~ 2.6
4-BG-25	750	1”	84	600 ~ 1200	20 ~ 50	1.5 ~ 2.6
4-BH-25	900	1”	84	600 ~ 1200	20 ~ 50	1.5 ~ 2.6